

JUE-87 Inmarsat C



– the JUE-87 is the latest all-new two-way Inmarsat C global data communication solution


- Compact all-in-one Internally Mounted Equipment with 10.4 inch display**
- Newly designed Externally Mounted Equipment with high performance RF filter**
- Single coax installation**
- Long Range Identification and Tracking (LRIT) as standard**
- JRC Remote Maintenance System (RMS) via LAN available**
- Optional Ship Security Alert System (SSAS)**
- USB mass storage device is available for messages exchange**

JUE-87

– flexibility


New Externally Mounted Equipment New

A completely new design of Externally Mounted Equipment (EME), compliant to RoHS, offering a new level of accuracy with a high performance Radio Frequency (RF) filter built in. It has the same cable management philosophy resembling all other Inmarsat products, requiring only a single coax cable between EME and IME.



Interfacing

The JUE-87 offers all the interfacing you need with junction box 1 (JB1) integrated in the bracket. In case of flush mounting, the bracket and junction box can be easily separated from the IME.



New accessories New

Along with our introduction of the new JUE-87, we introduce new accessories that compliment our unified design approach.



External buzzer

Distress button

Security button



New power supply New

JRC is introducing a new external power supply, half the size of the power supply found in the previous generation JUE-85 including a 65% weight reduction.

JUE-87

– operation

Enhanced Group Calling (EGC)

JRC total Inmarsat C solution incorporates the capability known as Enhanced Group Calling (EGC), which enables authorized information providers to broadcast international safety and commercial service messages to selected groups of ships. EGC is available as standard on the JUE-87 terminal.

EGC SafetyNET

An international safety service, which broadcasts maritime safety information, such as meteorological and hydrographic messages to all ships in certain geographical areas.

EGC FleetNET

An international commercial subscription service, allowing shipping companies and government bodies to broadcast messages to selected groups of vessels.



JCmail

JCmail is a freeware PC application developed by JRC. It enables you to send and receive e-mails and receive EGC messages very easily on the JUE-87.

Distress alert

Your vessel's ID, date/time and the present position, course and speed is acquired manually or automatically from the integrated GPS receiver, or the vessel's navigational interface, allowing you to send a distress alert simply by pressing and holding the dedicated built-in distress button, either on the IME or a separate unit.



LRIT as standard

The JUE-87 Inmarsat C model comes standard with Long Range Identification and Tracking (LRIT), an IMO required global monitoring system of the ship's movement. The purpose of LRIT is to increase maritime domain awareness and to improve maritime security.

SSAS add-on kit

The Ship Security Alerting System (SSAS) is a system that contributes to the IMO's efforts to strengthen maritime security and suppress acts of terrorism and piracy against shipping. In case of attempted piracy or terrorism, the vessel's SSAS function can be activated, and appropriate law-enforcement or military forces can be alerted if necessary.



JUE-87 Inmarsat C – maintenance

Self diagnosis

JRC JUE-87 Inmarsat C Mobile Earth Station(MES) incorporates various self-diagnostic programs to facilitate maintenance and troubleshooting, reporting any possible problems it might suffer. The results are displayed on the display of IME.

These functions allow for easy maintenance and more reliability. In addition, automatic testing for performance verification and commissioning via the satellite channel is also available.



Remote Maintenance System (RMS) New

JRC's unique RMS allows remote monitoring of bridge equipment from ashore. Using JRC VDR and INMARSAT FB satellite communication equipment, JRC can establish a highly secured connection to the vessel and cost-effectively and accurately determine the operating status of the JRC equipment while at sea.

JRC's RMS just got better with the addition of the new JUE-87 which allows connected satellite communication equipment's, such as JUE-251 & JUE-501, status to be polled from the shore.

JRC gloval service network(Star Network)

JRC has been providing sales and support of products since 1915.


Today, JRC offers comprehensive assistance through its organisation, in partnership with a worldwide StarNetwork™ of over 270 fully trained and qualified partners and agents, assisting you 24 hours a day, 7 days a week and 365 days a year.

**JRC one-call™**
One number to call
With JRC you can go anywhere and if you need our support, simply call us at +81 3 3492 9201, anytime.



JUE-87 Inmarsat C – configuration

System diagram



What's standard?

- IME (+JB1)
 - EME
 - Printer (+paper)
 - External Power supply
 - Cables
 - Installation materials
 - Spare parts
 - Manuals
- Signal
- EME to IME (30m)
 - IME to printer (2m)
- Power
- Power supply to IME (2.3m)
 - IME to printer (2m)

What's optional?

- Remote distress button NQE-3225
- External buzzer NCE-5547
- Security button NQE-3224
- Junction box 2 (JB2) NQE-3223
- Data terminal Equipment NDZ-227
- Keyboard NDF-369

JUE-87

– dimensions


EME New



NAF-253GM Mass 2.4kg



IME New




NTF-318 Mass 7.1kg, includes:
Messaging unit: 3.4kg
Junction box 1: 3.3kg
Keyboard: 0.4kg



Printer




NKG-800 Mass 3.7kg



External power supply New



NBD-904 Mass 2.6kg



JUE-87

– specifications

Model	JUE-87
Inmarsat type approved	✓ (Class 2)
RoHS	✓
Display	10.4 inch color LCD, 640x480 pixels 450cd/m ²
Frequency	TX : 1626.5 to 1646.5MHz RX : 1537.0 to 1544.2MHz
Channel spacing	5KHz
E.I.R.P.	14±2dBW (at 5° angle)
G/T	-23.0dB/K min
Modulation	TX/RX : 1200 symbols/sec BPSK
Data rate	TX/RX : 600bps
Interface	External Buzzer : 3ports (JB1x1, JB2x2) Remote distress button : 2ports (JB1x2) Security button : 4ports (JB1x2, JB2x2) GPS input (NMEA) : 1port (JB1) Alarm output (dry contact) : 1port (JB1) New Alarm output (NMEA) : 1port (JB1) New Alarm / AIS input (NMEA) : 1port (JB1) New LAN port (RJ-45) : 1port (IME) DTE port (serial) : 1port (IME) Keyboard : 1port (IME) Printer : 1port (IME) Serial : 1port (IME) Distress message controller : 1port (JB1)
Ambient condition	Operating: EME -35 to +55°C, IME -15 to +55°C Storage: EME/IME -40 to +70°C Relative humidity: 0 to 95% non-condensing Icing: up to 25mm (EME) Precipitation: up to 100mm/hour (EME) Wind: up to 100knots (EME)
Internally Mounted Equipment (IME)	
Model	NTF-318
Power	DC 24V (19.2 to 31.2V)
Consumption	Transmit: 100W, Standby: 15W
Externally Mounted Equipment (EME)	
Model	NAF-253GM (Unified pole mounting bracket)
Antenna	Type: helical, Pattern: hemisphere, Polarization: right-hand circular
Printer	
Model	NKG-800
Line interface	Parallel
Power	DC 24V (+19.2 to 31.2V)
Consumption	Approx. 35W
External power supply	
Model	NBD-904
Line Voltage	AC100 to 230V, DC24V
Line voltage selection	AC90 to 264V, DC19.2 to 31.2V
Output	DC24V 6.5A continuous
Option	
External buzzer	NCE-5547 (Max. 3units)
Remote distress button	NQE-3225 (Max. 2units)
Data terminal equipment	NDZ-227 (Max. 1unit)
Bracket for data terminal	MPBP31721
Keyboard for data terminal	NDF-369
Security button	NQE-3224 (Max. 4units)
Junction box2	NQE-3223
Wall mount adopter for buzzer/button	7ZZSC0095
Coaxial cable	CFQ-5922A4(40m), CFQ-5922A5(50m)

• Specifications may be subject to change without notice.

For further information, contact:



Since 1915

Japan Radio Co., Ltd.

URL <http://www.jrc.co.jp/eng/>

Main Office: Fujisawa bldg. 30-16, Ogikubo 4-chome
Suginami-ku, Tokyo 167-8540, Japan
Telephone: +81-3-6832-1816
Facsimile: +81-3-6832-1845

Overseas Branches : Seattle, Amsterdam, Athens, Manila
Liaison Offices : Taipei, Jakarta, Singapore, Hanoi,
Hamburg, New York

Overseas Subsidiaries : Shanghai, Rio de Janeiro

29EM

ISO9001, ISO14001 Certified